



skf P 35 RM Ball bearing plummer block units

Bearing No. P 35 RM

| | |
|-----------------------------------------|---------------|
| Bore Diameter | 35 mm |
| d | 35 mm |
| s1 | 23,3 mm |
| A | 41 mm |
| A1 | 27 mm |
| B | 33 mm |
| H | 78 mm |
| H1 | 39,2 mm |
| H2 | 5 mm |
| J | 106 mm |
| L | 130 mm |
| N | 11,2 mm |
| Thread (G) | 10 |
| Weight | 0,57 Kg |
| Basic dynamic load rating (C) | 25,5 kN |
| Basic static load rating (C0) | 15,3 kN |
| Housing material | Pressed steel |
| A ₁ | 27 mm |
| B ₄ | 6 mm |
| H ₁ | 39.3 mm |
| H ₂ | 5 mm |
| s ₁ | 23.3 mm |
| Basic dynamic load rating C | 25.5 kN |
| Basic static load rating C ₀ | 15.3 kN |
| Fatigue load limit P _u | 0.655 kN |
| Permissible radial housing | 3.3 kN |

P 35 RM Bearing 2D drawings and 3D CAD models



NTN BEARING MANUFACTURING DE MEXICO,S...

| | |
|---------------------------------------------------|------------|
| load max. | |
| Limiting speed | 5300 r/min |
| Mass bearing unit | 0.58 kg |
| Thread grub screw G ₂ | M6x0.75 |
| Hexagonal key size for grub screw N | 3 mm |
| Recommended tightening torque for grub screw | 4 N · m |
| Recommended diameter for attachment bolts, mm G | 10 mm |
| Recommended diameter for attachment bolts, inch G | 0.375 in |