



skf SY 1/2 TF Ball bearing plummer block units

Bearing No. SY 1/2 TF

SY 1/2 TF Bearing 2D drawings and 3D CAD models

Bore Diameter	12,7 mm
d	12,7 mm
s1	15,9 mm
A	32 mm
A1	18 mm
B	27,4 mm
G	10 mm
H	56 mm
H1	30,2 mm
H2	14 mm
J	97 mm
L	127 mm
N	20,5 mm
N1	11,5 mm
Weight	0,55 Kg
Basic dynamic load rating (C)	9,56 kN
Basic static load rating (C0)	4,75 kN
Fatigue load limit (Pu)	0,2
Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.59
EAN	7316577755544
Product Group	M06110



NTN BEARING MANUFACTURING DE MEXICO,S...

Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	YAR 203-008-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row Standard Duty Wide Inner Race Y Bearing Has Flinger
Long Description	2 Bolt Pillow Block; 1/2" Bore; 1-3/16" Base to Center Height; Set Screw Mount; Ball Bearing; 3-15/32" Minimum Bolt Spacing; 4-3/16" Bolt Spacing Maximum; Relubricatable; Cast Iron
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SY 1/2 TF
Weight / LBS	1.3
Bore	0.5 Inch 12.7 Millimeter
Base to Center Height	1.188 Inch 30.175 Millimeter
Bolt Spacing Maximum	4.188 Inch 106.375Millimeter



NTN BEARING MANUFACTURING DE MEXICO,S...

Actual Bolt Center to Center	0 Inch 0Millimeter
Nominal Bolt Center to Center	3.6 Inch 92 Millimeter
Bolt Spacing Minimum	3.469 Inch 88.113Millimeter
Length Thru Bore	1.094 Inch 27.8 Millimeter
Housing material	Cast iron
A ₁	18 mm
B ₄	4 mm
H ₁	30.2 mm
H ₂	14 mm
J max.	106 mm
J min.	88 mm
N ₁	11.5 mm
s ₁	15.9 mm
R _G	1/4-28 UNF
R ₁	1 mm
R	45 °
D _N	6.5 mm
SW _N	7 mm
G _N	1/4-28 SAE-LT
J ₆	118 mm
J ₇	11.5 mm
N ₄	2 mm
Basic dynamic load rating C	9.56 kN
Basic static load rating C ₀	4.75 kN
Fatigue load limit P _u	0.2 kN
Limiting speed	9500 r/min
Mass bearing unit	0.48 kg
Thread grub screw G ₂	#10-32 UNF
Hexagonal key size for grub screw N	2.381 mm



NTN BEARING MANUFACTURING DE MEXICO,S...

Recommended tightening torque for grub screw	4 N · m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in