



skf P 30 TR Ball bearing plummer block units

Bearing No. P 30 TR

Bore Diameter	30 mm
d	30 mm
s1	22,2 mm
A	38 mm
A1	25 mm
B	38,1 mm
H	66 mm
H1	32,9 mm
H2	4 mm
J	95 mm
L	119 mm
N	11,2 mm
Thread (G)	10
Weight	0,47 Kg
Basic dynamic load rating (C)	19,5 kN
Basic static load rating (C0)	11,2 kN
Housing material	Pressed steel
A ₁	25 mm
B ₄	5 mm
H ₁	33 mm
H ₂	4 mm
s ₁	22.2 mm
Basic dynamic load rating C	19.5 kN
Basic static load rating C ₀	11.2 kN
Fatigue load limit P _u	0.475 kN
Permissible radial housing	2.6 kN

P 30 TR Bearing 2D drawings and 3D CAD models



NTN BEARING MANUFACTURING DE MEXICO,S...

load max.	
Limiting speed	3800 r/min
Mass bearing unit	0.45 kg
Thread grub screw G ₂	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N · m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in