



## skf P 30 TF Ball bearing plummer block units

Bearing No. P 30 TF

Bore Diameter	30 mm
d	30 mm
s1	22,2 mm
A	38 mm
A1	25 mm
B	38,1 mm
H	66 mm
H1	32,9 mm
H2	4 mm
J	95 mm
L	119 mm
N	11,2 mm
Thread (G)	10
Weight	0,47 Kg
Basic dynamic load rating (C)	19,5 kN
Basic static load rating (C0)	11,2 kN
Category	Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
UNSPSC	31171544
Weight / Kilogram	0
EAN	7316570994988
Product Group	M06110
Housing material	Pressed steel
A <sub>1</sub>	25 mm

P 30 TF Bearing 2D drawings and 3D CAD models



## NTN BEARING MANUFACTURING DE MEXICO,S...

B <sub>4</sub>	5 mm
H <sub>1</sub>	33 mm
H <sub>2</sub>	4 mm
s <sub>1</sub>	22.2 mm
Basic dynamic load rating C	19.5 kN
Basic static load rating C <sub>0</sub>	11.2 kN
Fatigue load limit P <sub>u</sub>	0.475 kN
Permissible radial housing load max.	2.6 kN
Limiting speed	6300 r/min
Mass bearing unit	0.45 kg
Thread grub screw G <sub>2</sub>	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N · m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in